		Airflow		Installation		Heat Recovery				Frost Protection						Air Treatment						Quality								Configuration							Options													
		Minimum	Maximum	Indoor	Outdoor	Polypropylene	Aluminum	Enthalpic	Enthalpy Wheel	Fan exhaust	Recirculation	Face and bypass damper	Electric pre-heat coil	Hot water pre-heat coil	VFD on Wheel	Electric post-heating coil	Hot water post-heating coil	Chilled water cooling coil	DX cooling coil	HSF: High-Strength Frame System	No thermal bridges	No penetrating screws	Double-wall cabinet	Control panel with power and control separated	Roof with rain gutter	Access door with automotive quality seal	Paint finish with layer of silicone polyester	Wiring protected by flexible sheath	Pre-drilled hole for power grid connection	One-side access door	Low Profile	Custom modifications	1-inch Insulation (R4)	2-inch Insulation (R8)	2.5-inch Insulation (R10)	Pool construction	Roof curb (standard or insulated)	Drive assembly/Blower on vibration isolating rubber	Drive assembly/Blower on vibration isolating springs	Pillow block bearing fan	HE Filter replacement	HF filter adding	Insulated motorized dampers	Backdraft damper	BACnet-compatible controller	VFD on motors	Low temperature limit	Dirty filter dry contact	Low airflow switch	Phase-loss detection	Damper end-switch	CO2/RH Sensor	EC Motors
LOW PROFILE	LH2000i/e	1000	2500	X	X	X	X			X	X		X	X		X	X					S	S	S		S	X	S	X		S		i-S	e-S		X	e-X	S	X		X	X	X	X	X	X	X	X	X	X	X	
	LH3000i/e	2000	3500	X	X	X	X			X	X		X	X		X	X					S	S	S		S	X	S	X		S		i-S	e-S		X	e-X	S	X		X	X	X	X	X	X	X	X	X	X	X	
	LE2000i/e	1000	2500	X	X			S		X	X		X	X		X	X					S	S	S		S	X	S	X		S		i-S	e-S		X	e-X	S	X		X	X	X	X	X	X	X	X	X	X	X	
	LE3000i/e	2000	3500	X	X			S		X	X		X	X		X	X					S	S	S		S	X	S	X		S		i-S	e-S		X	e-X	S	X		X	X	X	X	X	X	X	X	X	X	X	

S : standard i-S : standard interior machine
X : option e-S : standard exterior machine e-X : option exterior machine