



AIRFLOW & ZONE CONTROLS
CAR-IIA
 Adjustable Constant Airflow Regulator

PRODUCT
 SPECIFICATIONS
 & TECHNICAL
 DATA



Adjustable Constant Airflow Regulators (CAR-IIA) can be field adjusted to the desired airflow by removing the aero-clips. Each clip removed increases the free-area opening, allowing more air to pass through the device.

DIAMETER	PART NUMBER	REGULATED CFM			
		0 CLIPS REMOVED *	1 CLIP REMOVED	2 CLIPS REMOVED	3 CLIPS REMOVED
4"	18 110A	10	15	25	--
	18 111A	10	20	30	--
	18 115A	35	45	50	--
	18 109A	40	50	60	--
5"	18 121A	35	45	50	--
	18 124A	75	90	105	--
6"	18 131A	75	90	105	--
	18 134A	125	140	160	175
8" **	18 141A	125	140	160	175
	18145A	205	235	265	295
10"	18 151A	205	235	265	295
	18 155A	325	355	380	410

*** IMPORTANT:** All Adjustable CAR-IIs are shipped at the "0 Clips Removed" setting.

**** NOTE:** To increase the airflow in the 8" CAR-IIA, simply move the aero-clip to the next higher notch.

© 2013 American ALDES Ventilation Corporation. Reproduction or distribution, in whole or in part, of this document, in any form or by any means, without the express written consent of American ALDES Ventilation Corporation, is strictly prohibited. The information contained within this document is subject to change without prior written notice.

American ALDES Ventilation Corporation • 4521 19th Street Court East, Suite 104 • Bradenton, FL 34203 – USA
 941.351.3441 • 800.255.7749 • 941.351.3442 (fax) • info@americanaldes.com • www.americanaldes.com

CAR-IIA_spec_0813