




## AIRFLOW & ZONE CONTROLS

# CAR-SE-II

## Constant Airflow Regulator for Square or Rectangular Ducting in Exhaust or Return Air Applications

## PRODUCT SPECIFICATIONS & TECHNICAL DATA



### GENERAL

The model CAR-SE-II Constant Airflow Regulator is a modulating orifice that automatically regulates airflows in duct systems to constant levels. The passive control element responds to duct pressure and requires no electric or pneumatic sensors or controls.

The CAR-SE-II compensates for changes in duct pressure caused by thermal stack effect, building pressure, dust-clogged filters, etc. The CAR-SE-II also provides a low-cost solution to balancing forced-air systems for heating, air conditioning and ventilation, eliminating the need for on-site balancing. The CAR-SE-II will regulate airflow in exhaust or return duct systems.

The active control element of the CAR-SE-II is a unique aerofoil (CAR-II). Using Bernoulli's Principle, the aero-wing damper lifts in response to increasing static pressure. This operation regulates the free-area opening through the control, resulting in maintenance of velocity and specific airflow set points. Each CAR-II is designed and produced for control of air in temperatures ranging from -25°F to 140°F (-32°C to 60°C).

### CONSTRUCTION

The round CAR-II is constructed of a UL94V-0 ABS plastic, and it is UL 2043 safety classified and labeled for flame and smoke generation. The assembly is sized to fit inside standard square or rectangular ducting, as well as register boots, return grille collars, etc. Each mounting plate is designed to specifically accommodate the control element and prevent unwanted air leakage.

### PERFORMANCE

The CAR-II airflow regulators control airflow accurately to within 10% of rated flow (15% for units 50 CFM or

less) throughout the target operating pressure range of 0.2 to 0.8 in. w.g. (50 to 200 Pa). Each CAR-II is factory tested and calibrated to the rated set point before shipping. Each diameter of the CAR-II regulator is available in multiple factory-calibrated set points (see performance curves).


### MAINTENANCE

The CAR-II needs no maintenance when used in normal conditions. There is no risk of dust deposit or obstruction because the CAR-II has no airways subject to clogging. If the intended application includes air heavily loaded with grease or dust, a fitting with an access panel or door, such as that used for flame dampers, should be provided.

### WARRANTY

Guaranteed for 5 years, from date of shipment, against all defects in material or workmanship, provided that the material has been installed and used under normal conditions. This warranty is limited to the repair or replacement of the material.

## CAR-SE-II Dimensions




PART NUMBER	NOMINAL DUCT SIZE*	REGULATING ELEMENT SIZE	A	B	C
19 101	6" x 4"	4"	5.9"	3.9"	2.5"
19 102	6" x 6"	4"	5.9"	5.9"	2.5"
19 103	6" x 6"	5"	5.9"	5.9"	3.5"
19 104	6" x 6"	6"	5.9"	5.9"	3.5"
19 105	8" x 8"	4"	7.9"	7.9"	2.5"
19 106	8" x 8"	5"	7.9"	7.9"	3.5"
19 107	8" x 8"	6"	7.9"	7.9"	3.5"
19 108	8" x 8"	8"	7.9"	7.9"	3.5"
19 109	10" x 10"	4"	9.9"	9.9"	2.5"
19 110	10" x 10"	5"	9.9"	9.9"	3.5"
19 111	10" x 10"	6"	9.9"	9.9"	3.5"
19 112	10" x 10"	8"	9.9"	9.9"	3.5"
19 113	10" x 10"	10"	9.9"	9.9"	3.8"
19 114	12" x 12"	4"	11.9"	11.9"	2.5"
19 115	12" x 12"	5"	11.9"	11.9"	3.5"
19 116	12" x 12"	6"	11.9"	11.9"	3.5"
19 117	12" x 12"	8"	11.9"	11.9"	3.5"
19 118	12" x 12"	10"	11.9"	11.9"	3.8"

\* Standard sizes shown.

Mounting plates are also available to accommodate any rectangular duct size.

## How the CAR-II Works

Constant airflow is achieved by controlling the free area through the device. At minimum static pressure, the aero-wing is parallel to the air stream. As the static pressure increases, the aero-wing lifts, reducing the amount of free area through the regulator. At the same time, higher static pressure increases the air velocity resulting in **CONSTANT AIRFLOW**. This occurs regardless of pressure differences in the range of 0.2 to 0.8 in. w.g. (50 to 200 Pa). The air velocity in the duct is in the range of 60 to 700 ft/min. (0.3 to 3.5 m/s).



## Typical CAR-SE-II Applications

- Exhaust air in offices.
- Balancing exhaust airflows in high-rise building duct risers.
- Bathroom exhaust in nursing homes, hotels, motels, dormitories, apartment buildings, offices, etc.
- Balancing exhaust of heat recovery ventilation systems.
- Balancing airflows on series-fan-powered terminal unit systems.

## Typical Specification


Model CAR-SE-II Constant Airflow Regulators by American ALDES Ventilation Corporation, Bradenton, Florida, shall solely operate on duct pressure and require no external power supply. Each regulator shall be pre-set and factory calibrated, requiring no field adjustment to the airflows as indicated on the schedule, and shall be rated for use in air temperatures ranging from -25° to 140°F (-32° to 60°C.)

Constant Airflow Regulators shall be capable of maintaining constant airflow within +/- 10% of scheduled flow rates (15% for units 50 CFM or less), within the operating range of 0.2 to 0.8 in. w.g. differential pressure, or 0.6 to 2.4 in. w.g. on high-pressure models (CAR-HP-SE-II), or 0.1 to 0.42 in. w.g. on low-pressure models (CAR-LP-SE-II). Regulators shall be provided as an assembly consisting of a steel mounting plate with collar and a 94V-0 UL ABS plastic body housed within a round sleeve for installing in mounting plate collar. Each round sleeve must be fitted with a lip gasket to ensure perimeter air tightness with the interior surface of the duct. All regulators must be classified per UL 2043 and carry the UL mark indicating compliance. All Constant Airflow Regulators will require no maintenance and must be warranted for a period of no less than five years. Constant Airflow Regulators shall be installed in tight ducting systems in accordance with all applicable codes and manufacturer's instructions.


# CAR-SE-II Airflow Performance Data

Performance charts reflect airflow measurements taken at 68°F (20°C) at 1 atmosphere pressure. The CAR-SE-II is designed for system pressures between 0.2 and 0.8 in. w.g. Models are also available for applications with system pressures between 0.1 and 0.42 in. w.g (CAR-LP-SE-II) and above 0.8 in. w.g. (CAR-HP-SE-II).


## 4" DIAMETER (100 mm) REGULATING ELEMENT



## 5" DIAMETER (125 mm) REGULATING ELEMENT




## 6" DIAMETER (150 mm) REGULATING ELEMENT



# CAR-SE-II Airflow Performance Data

Performance charts reflect airflow measurements taken at 68°F (20°C) at 1 atmosphere pressure. The CAR-SE-II is designed for system pressures between 0.2 and 0.8 in. w.g. Models are also available for applications with system pressures between 0.1 and 0.42 in. w.g (CAR-LP-SE-II) and above 0.8 in. w.g. (CAR-HP-SE-II).

## 8" DIAMETER (200 mm) REGULATING ELEMENT



## 10" DIAMETER (250 mm) REGULATING ELEMENT

