



LIGHT COMMERCIAL
H1800A-Fi & H1800A-Ri
Heat Recovery Ventilator
400-1700 CFM Range

PRODUCT
SPECIFICATIONS
& TECHNICAL
DATA



H1800A-Fi & H1800A-Ri

The H1800A ventilator provides high-efficiency heat recovery. The unit uses a durable aluminum core that can withstand a wide range of environmental conditions. The H1800A produces approximately **1675 CFM** at 0.20 in.w.g (ESP). It is powerful enough for restaurants, offices, and other small businesses.

The H1800A is ideal for cold-weather applications. The H1800A-Fi shuts down the fan for the outdoor air supply during defrost cycles, while the H1800A-Ri uses a fifth port with a motorized damper to defrost the core with recirculated warm air from inside the building.

FEATURES

- Plate-type aluminum cores
- Quiet operation
- Multiple filter options
- Efficient and economical operation
- Indoor application

CASING

Material: Painted galvanized steel
Insulation: 1"(25 mm)
Drain Connection: Ø 1/2" (Ø 13 mm)
Duct Connections: 24" x 8" (610 mm x 203 mm)
Width: 45-5/8" (1158 mm)
Height: 29-5/8" (753 mm)
Depth: 48-7/8" (1242 mm)
Unit Weight: 245 lbs (111 kg); 258 lbs (117 kg) with recirculation
Shipping Weight: 300 lbs (136 kg)
313 lbs (142 kg) with recirculation

PLATE EXCHANGER

Standard: Aluminum (sensible heat transfer)
Quantity: 3
Pitch: 0.13" (3.3 mm)
Dimensions: 16.34" x 16.34" x 15.67"
(415 mm x 415 mm x 398 mm)



MOUNTING

Supplied with base rails. Support rod by others.

BLOWERS

Quantity: 4
Type: Backward-inclined motorized impeller, direct-drive PSC, variable speed, external rotor

FILTERS

Number: 6
Type: Aluminum (P/N: 612414)
Optional: MERV 8 (P/N: 612411), Carbon (P/N: 612413), or High Efficiency/MERV13 Equivalent (P/N: 612412)

Additional Air Pressure Drop with Optional Filters				
Filter Type	Airflow CFM (m³/h)			
	600 (1020)	1000 (1700)	1400 (2380)	1800 (3060)
MERV 8	0.04	0.08	0.15	0.22
Carbon	0.04	0.08	0.15	0.22
High Efficiency	0.22	0.35	0.48	0.63

ELECTRICAL REQUIREMENTS

120 VAC, 60 Hz, 14.2 A, 1589 W
20A breaker required

FROST CONTROL

Cycles controlled by a temperature sensor when outdoor temperatures fall below 23°F (-5°C).

- Standard: Exhaust Defrost (H1800A-Fi)
- Optional: Recirculation Defrost (H1800A-Ri)

CONTROLS

24 VAC, 10 VA output for supply and exhaust dampers
Low-voltage dry contact (24 VAC, 20 VA) for:

- Occupancy Control (start/stop)
- Fan Interlock (NO and NC)
- Speed Selection
- Exhaust/Recirculation (with H1800A-Ri)

Compatible With:

- Digital Multifunction Control (P/N: 611242FC)
- Mode Control (exchange or recirculation) (P/N: 611230)
- Humidity Control (P/N: 611224)
- Speed Control (Low/Intermittent/High) (P/N: 611229)
- 20/40/60 Minute Timer (P/N: 611228)


APPROVALS

Meets Standards:
• UL 1812 and C22.2 no113


Listed:




Dimensions



FRONT VIEW




BOTTOM VIEW




SIDE VIEW

Performance

H1800A-Fi Ventilation Performance



H1800A-Fi & H1800A-Ri Core Efficiency



© 2016 American ALDES Ventilation Corporation. Reproduction or distribution, in whole or in part, of this document, in any form or by any means, without the express written consent of American ALDES Ventilation Corporation, is strictly prohibited. The information contained within this document is subject to change without prior written notice.

American ALDES Ventilation Corporation • 4521 19th Street Court East, Suite 104 • Bradenton, FL 34203 – USA
941.351.3441 • 800.255.7749 • 941.351.3442 (fax) • info@americanaldes.com • www.aldes.us