

Intertek
C22.2 no113
UL 1812

LIGHT COMMERCIAL SERIES

ERV

E1800L-Fi-EC-N

Energy Recovery Ventilator

1925 CFM at 0.4 in.w.g (ESP)



CORE

OTHER
PARTS

PRODUCT DESCRIPTION

The E1800L-Fi-EC-N energy recovery ventilator provides up to 1925 cubic feet per minute of fresh outdoor air while exhausting an equivalent amount of stale indoor air, creating a well-balanced ventilation system. The E1800L-Fi-EC-N makes use of Aldes' AHRI Certified High Latent Transfer enthalpic cores that deliver superior moisture transfer and can be used in any climate zone. The highly efficient and quiet variable-speed EC motors use on average 50% less electricity of the E1800L-Fi-N at low speed, significantly increasing return on investment.

The E1800L-Fi-EC-N is recommended for mid-sized non-residential spaces or dedicated zones within larger buildings such as classrooms, common areas of residential complexes and indoor parking garages.

Designed for versatile indoor installation, Aldes light commercial ventilators can fit almost anywhere and still provide easy access to the internal components for quick maintenance. The units also offer a choice of five continuous operation speeds and a demand-controlled high speed exchange mode.

KEY FEATURES

Electronically and independently adjustable supply and exhaust blowers (FlexControl).

Painted, heavy-gauge galvanized steel cabinets are attractive, rust-resistant and extremely durable.

Doors on both sides of the unit to allow easy access to filters, cores and motors, no matter the installation constraints.

Fan exhaust frost protection, or optional recirculation defrost kit (factory installed or upgraded in the field).

Four highly efficient and noise reducing RadiCal centrifugal fans with EC motors from EBM Papst.

Durable High Latent Transfer enthalpy core has exceptional moisture transfer for increased comfort.



Plate Exchanger

Material: High latent transfer (HLT)

Casing

Material: Painted galvanized steel 22GA

Insulation: 1" (25 mm) Fiberglass with FSK

Drain Connection: Ø 1/2" (Ø 13 mm)

Duct Connections: 20" x 8" (508mm x 203mm)

Width: 45-5/8 (1158mm)

Height: 29-5/8 (753mm)

Depth: 48-7/8 (1242mm)

Unit Weight: 245 lb (111 kg); 258 lb (117 kg) with recirculation



Mounting

Supplied with base rails. Support rods by others.



Electrical Requirements

230V/1p/60 Hz: FLA 8.8A, MCA 9.4A, MOP 15A

208V/1p/60 Hz (with field modification): FLA 9.6A, MCA 10.2A, MOP 15A

Terminal block for direct wiring to the building's electrical system.

Fused disconnect not included.



Frost Control

Cycles controlled by a temperature sensor when outdoor temperatures fall below 14°F (-10°C).

- Standard: Exhaust Defrost
- Optional: Recirculation Defrost (P/N 683950)



Blowers

Four backward-inclined motorized impeller, direct drive EC motor, variable speed, external rotor.



Filters


Type : Aluminum (P/N 683907)

Optional : MERV 8 (P/N 683906), Charcoal (P/N 683908), or High Efficiency/MERV13 Equivalent (P/N 683909)

Additional Air Pressure Drop with Optional Filters

Filter Type	Airflow CFM (L/S)	
	1000 (472)	1800 (850)
MERV 8	0.08	0.22
Charcoal	0.08	0.22
High Efficiency	0.35	0.63

Dimensions



Controls


0-10 VDC inputs (for supply and exhaust) or multiple fixed speed options

Low-voltage dry contact (24 VAC, 20 VA) for:


- Occupancy Control (On/Off)
- Interlock contacts
- Optional Recirculation Mode

24 VAC, 10 VA output for supply and exhaust dampers (by others)

Compatible with :



Digital Multifunction Control
(P/N 611242-FC)



LCD Electronic Multifunction Control
(P/N 611227)



20/40/60 Minute Timer (P/N 611228)





Speed Control (Low/Intermittent/High)
(P/N 611229)



Mode Control (exchange or
recirculation) (P/N 611230)

BACnet™ interface (P/N 611235)

Performance



Project:		Architect:	
Location:		Engineer:	
Model #:		Contractor:	
Quantity:		Comments:	
Submitted By:			
Date:			

For more information, contact your Aldes sales advisor, visit aldes-na.com, call 1.800.255.7749, or find us on

