



**HEAT & ENERGY RECOVERY**

---



## **Commercial Heat & Energy Recovery**

---

500-11000 CFM

TECHNICAL COMMERCIAL DOCUMENTATION

## COMMERCIAL HRV/ERV

# Building Air Quality

What do you consider when selecting a Heat or Energy Recovery Ventilator for a commercial project? Cost, code compliance, performance, size, airflow, custom options, compatibility with other HVAC equipment, production time, installation cost, maintenance, warranty, equipment life expectancy, return on investment, or all of the above? What about the fundamental concerns: Will this product do what the manufacturer claims? Will the building occupants benefit from increased comfort and improved indoor air quality? Is it a good investment?

ALDES knows that HRV/ERV decisions are never taken lightly. That's why we manufacture our Commercial HRV/ERVs with the features you need, the performance you expect, and the superior build quality you deserve. We offer all available types of air-to-air heat exchangers in a variety of price points and configurations. Every job is custom-built to your exact design parameters. We want it to be painless to specify an ALDES unit. We want you to be confident in your choice—from the moment you make the selection to years after installation. ALDES has more than 30 years of experience providing the finest ventilation solutions in North America. Your business is our pleasure. Your satisfaction is our priority.

## WHY CHOOSE A COMMERCIAL HRV/ERV



## COMMERCIAL RANGES

### Advanced Commercial Series

The customized solution



### InspirAIR® Commercial Series

The turnkey solution

Nominal Capacity	500-4000 CFM	1000-11000 CFM
Interior Models	X	X
Exterior Models	X	X
Aluminum Core	X	X
Polypropylene Core	X	X
Enthalpic Core	X	X
Desiccant Wheel	X	X
Fan Exhaust Defrost	X	X
Recirculation Defrost	X	X
Pre-Heat Coils (Electric & Hot Water)	X	X
Face & Bypass Damper	X	X
Wheel Speed VFD	X	X
Electric Post-Heating Coils	X	X
Hot Water Post-Heating Coils	X	X
Cold Water Cooling Coils		X
DX Cooling Coils		X

---

## ALDES SELECTOR™ SOFTWARE

---



Selector™ puts you in the designer's seat and ensures a better finished product

- Select models based on your exact design conditions and parameters
- Compare similar Commercial Series units for the best fit
- Receive detailed submittals for your unit
- Generate project schedules to indicate critical performance data
- Share designs and import projects directly into the software
- Streamline your workflow

*Selector™ is available by request. Contact your ALDES sales advisor.*



---


## TYPICAL APPLICATIONS

---



Offices • Hotels • Hospitals • Schools • Shopping Centers  
Restaurants • Casinos • Dormitories • Auditoriums • Pools & Spas  
Warehouses • Animal Care Facilities • Laboratories • Manufacturing Plants  
Retirement Homes • Day Care Centers • Correctional Facilities  
Religious Spaces • Theatres • Health Clubs

## Reading the Model Code



MODELS		
CH2000i/e	CE2000i/e	CW2000i/e
CH3000i/e	CE3000i/e	CW3000i/e
CH5000i/e	CE5000i/e	CW5000i/e
CH6500i/e	CE6500i/e	CW6500i/e
CH8000i/e	CE8000i/e	CW8000i/e
CH10000i/e	CE10000i/e	CW10000i/e

*\*Wheel capacities vary slightly.  
Please see spec sheets for CFM ranges.*

## Interior Model




## Exterior Model



## Duct Configurations

### All Plate Models




AVAILABLE DUCT CONFIGURATIONS*		AVAILABLE DUCT CONFIGURATIONS*	
1 - 2 - 6 - 7		3 - 4 - 7 - 8	1 - 4 - 7 - 8
1 - 3 - 5 - 7		3 - 4 - 6 - 7**	1 - 4 - 6 - 7**
1 - 3 - 6 - 7		1 - 2 - 7 - 8	2 - 3 - 7 - 8
1 - 2 - 5 - 7		1 - 2 - 6 - 7**	2 - 3 - 6 - 7**

DUCT CONNECTION KEY		DUCT CONNECTION KEY	
1	OUTDOOR AIR	1, 3	SUPPLY AIR
2, 3	RETURN AIR	2, 4	RETURN AIR
5, 6	SUPPLY AIR	6, 8	EXHAUST AIR
7	EXHAUST AIR	7	OUTSIDE AIR


### All Wheel Models



\* Mirror image cabinet also available

\*\* Configuration not available for exterior models

## KEY FEATURES



### Additional Features

- Automotive-Quality Door Seal
- Single-Point Power Connection
- No-Screw-Through Design
- Thermal Bridging Breaks
- Insulation Value of R-10
- Conduit-Sleeved Cable Protection
- Multiple Duct Configurations
- EPAct or Premium Efficiency Motors
- Adjustable Speed Motors
- Pre-Wired Control Panel with Separated High and Low Voltages
- Front or Back Piping Connections
- Baked Enamel Exterior Finish
- Non-Fused Disconnect
- ETL Listed

### Optional Features

- "Pool Construction Package" (stainless steel interior, epoxy-coated blowers, totally enclosed motors)
- Heavy-Gauge Steel Roof Curb (optional insulation)
- Fan Exhaust Defrost, Recirculation, Pre-Heat Coils (Electric or Hot Water), Face and Bypass Damper, and Wheel Speed VFD\*
- Electric or Hot Water Post-Heat Coils
- Cold Water or DX Cooling Coils
- MERV 13 Final Filters
- Backward-Inclined Blowers
- Mirror Image Cabinet
- Motorized and Insulated Dampers for Exhaust and Outdoor Air Openings
- Fused Disconnect
- Non-Insulated Backdraft Damper
- Mechanical Purge\*

- Low Temperature Limit
- Economizer Cycle
- Dirty Filters Contact
- Low Airflow Switch
- Phase Loss Detection
- Wheel Rotation Detection\*
- Damper End Switch
- Programmable Timer
- CO<sub>2</sub> and/or Relative Humidity Sensor
- BACnet Compatible Controller (IP or MS/TP communications protocol)
- Remote Keypad (optional touchscreen)

\*Wheel models only

## Reading the Model Code

**Example** P E 15

### SERIES

InspirAIR® Commercial

### RECOVERY TYPE

Sensible & Latent - HLT Plate (E)  
Sensible & Latent - Wheel (W)  
Sensible Only - Aluminum Plate (A)  
Sensible Only - Polypropylene Plate (H)

### NOMINAL CAPACITY

500-1000 CFM (15)  
800-2000 CFM (20)  
1000-3000 CFM (30)  
2000-4000 CFM (40)

## MODELS

PA15	PA20	PA30	PA40
PE15	PE20	PE30	PE40
PH15	PH20	PH30	PH40
PW15	PW20	PW30	PW40

## Interior Model



## Exterior Model



## Duct Configurations


### AVAILABLE DUCT CONFIGURATIONS\*

1 - 2 - 5 - 6

1 - 3 - 4 - 6\*\*

\* Mirror image cabinet also available

\*\*Available on exterior units only



### DUCT CONNECTION KEY

1	EXHAUST AIR
2, 3	SUPPLY AIR
4, 5	RETURN AIR
6	OUTSIDE AIR

## KEY FEATURES

Top & Bottom Blower Configuration

AMCA-certified low-leakage dampers and optional weather hoods with bird screens

Robust double wall construction

MERV 8 or MERV 13 filters

Efficient EC Motors

Bypass damper for free cooling

AHRI Certified heat recovery

Plate unit showing all the extensions - bypass, pre- and post heating and with AC motors.

All components easily accessible for maintenance

### Additional Features

- Automotive-Quality Door Seal
- Single-Point Power Connection
- No-Screw-Through Design
- Insulation Value of R-4.3
- Conduit-Sleeved Cable Protection
- Four Duct Configurations
- Non-Fused Disconnect
- ODP or TEFC Type Motors
- EPAAct or Premium Efficiency Motors
- Adjustable Speed Motors
- Pre-Wired Control Panel with Separated High and Low Voltages
- ETL Listed

### Optional Features

- Baked Enamel Exterior Finish
- Heavy-Gauge Steel Roof Curb (optional insulation)
- Fan Exhaust Defrost, Recirculation Defrost, Electric or Hot Water Pre-Heat Coils, Wheel Speed Defrost
- EC Motors
- Electric or Hot Water Post-Heat Coils
- MERV 13 Supply Filters
- Fused Disconnect
- Mirror Image Cabinet
- Motorized and Insulated Dampers for Exhaust and Outdoor Air Openings
- Non-Insulated Backdraft Damper
- Additional 24 VAC, 20 VA power connection for accessories
- Internal bypass for free cooling

- Low Temperature Limit
- Dirty Filters Contact
- Low Airflow Switch
- Phase Loss Detection
- Damper End Switch
- Programmable Timer
- BACnet Compatible Controller (IP or MS/TP communications protocol)
- Remote Keypad (optional touchscreen)
- Wheel Rotation Detection



For more information, contact your  
ALDES sales advisor, visit [ALDES-na.com](http://ALDES-na.com),  
or find us on



ALDES North America  
USA 800.255.7749 CAN 800.262.0916

