Faldes









PLATE EXCHANGER

High-efficiency polymeric membrane counter-flow ERV

CASING (Standard)

Material: 24-gauge galvanized steel Drain connections: optional Duct connections: 5"(127 mm) Insulation: EPS molded polystyrene

Length: 23" (584.2 mm) Height: 19" (482.6 mm) Width: 16" (406.4 mm) Weight: 51 lb (23 kg)

Exhaust Damper: Closed by gravity

Swivel ports for horizontal, vertical, oblique or mixed

installations.



MOUNTING

Mounting chains included Wall mounting optional (P/N 699878)



ELECTRICAL SPECIFICATIONS

120 V, 60 Hz, 181 W, 2.46 A



FILTERS

(Standard)

Quantity:

2 washable MERV 6 filters (P/N 699771) Optional filter types: MERV 8 (P/N 699772),

MERV 13 (P/N 699881)



SYSTEM COMPATIBILITY

Compatible with VentZone System

InspirAIR® ELITE

ERV

EK150-TF-V5

148 CFM at 0.4 in.w.g












UNIT

CORE

BLOWERS & MOTORS





DEFROST

Automatic Programmed Recirculation: Cycles are controlled by a temperature sensor when the outside temperature drops below 10.4°F (-12°C).

WARRANTY

Limited 5 years on the cores and all covered components.

WALL CONTROLS

Low voltage dry contact (24VAC) for interlock with heating and cooling systems. For more details, please refer to the wall control specification sheets.



Digital Multifunction Control (P/N 611242-FC)



LCD Electronic Multifunction Control (P/N 611227)



20/40/60 Minute Timer (P/N 611228)



Speed Control (Low/Intermittent/High) (P/N 611229)




Mode Control (Recirculation) (P/N 611230)




Page 2 | EK150-TF-V5


TOP VIEW



FRONT VIEW








EK150-TF-V5: PERFORMANCE

EK150-TF-V5 Ventilation Performance



Thermal Performance – EK150-TF-V5								
Supply Tem- perature		Net Airflow		Power Consu- med	Sensible Recovery	Adjusted Sensible	Latent Recovery/	Total Recovery
°F	°C	CFM	L/s	(w)	Efficiency	Recovery Efficiency	Moisture Transfer	Efficiency
Heating								
32	0	50	23	60	82%	91%	89%	-
32	0	65	30	71	82%	90%	86%	-
14	-10	65	30	69	81%	86%	85%	-
Cooling								
95	35	64	30	71	-	-	83%	76%

Project:	Architect:
Location:	Engineer:
Model #:	Contractor:
Quantity:	Comments:
Submitted By:	
Date:	



